



Dell Edge Gateway 5000 Series



Collect, analyze, relay and act on Internet of Things data at the edge of the network with this IoT gateway purpose-built for Building and Industrial Automation.

Analytics at the edge

The Dell Edge Gateway 5000 Series is designed to aggregate, secure and relay data from diverse sensors and equipment. The Intel® Atom™ processor provides capacity to perform local analytics so only meaningful information is sent to the next tier, which could be another gateway, the datacenter or the cloud. This minimizes consumption of expensive network bandwidth and reduces overall solution latency.

For IT and Operations Technology

Unlike PCs and servers, the Dell Edge Gateway 5000 Series is designed to attach to a wall or DIN rail in commercial and industrial environments. Combine the gateway with Dell's IT expertise, choice of operating system, and software from our certified, operations-focused ISV partners to meet the needs of both IT and Operations Technology (OT) organizations.

Tough for many environments

Engineered with an industrial-grade form factor and fanless, solid-state design, the Dell gateway can reliably run 24x7 with long life at extended temperatures, in addition to withstanding the higher levels of humidity and dust typical of industrial environments. The Model 5700 supports an extended temperature range making it perfect for use in extreme conditions such as boiler rooms or inside rooftop HVAC units.

Dell Services and Support

Dell offers a complete services solution for the Dell Edge Gateway 5000 Series, including Basic Hardware Support and ProSupport to provide end-to-end hardware support throughout the product lifecycle. Plus, with our Configuration Service we can configure gateways to your specifications, including custom BIOS settings and factory installation of your software image.

Expanded I/O and communication protocols

Make the most of the equipment you already have and expand capabilities with new technologies. Connect broadly with the physical world using Dell IoT gateways, bridging both legacy systems and modern sensors to the internet. With the right physical I/O and our certified ISV middleware, you can aggregate and normalize virtually any data source, ranging from legacy protocols such as BACNet, Modbus, and CANbus, to modern wireless mesh networks like Zigbee, 6LoWPAN, and ZWave.

Security built in

You can depend on Dell's broad IT security portfolio. Dell's gateways feature a TPM chip for hardware root of trust, secure boot, and BIOS-level lockdown of unused I/O ports. Security is as much about best practices as it is features, and Dell offers expertise to build security measures throughout your solution.

Flexibility and manageability

Dell IoT gateways are designed for the flexible manageability that IT requires. WindRiver is supported by Helix Device Cloud, and Ubuntu and Windows IoT customers get their choice of Dell Cloud Client Manager (CCM) or a third-party on-premise console such as Microsoft System Center, backed by the Dell Command Client Suite for both Linux and Windows.

Co-branded or end-to-end

The gateway can be co-branded and integrated into your own smart systems, or ask us to enable a **full IoT system** for your specific business need. Talk to us about our cloud, servers, storage, networking and mobility solutions for IoT. We are experts in manageability, security, data integration, analytics, and services for end-to-end IoT solutions.

	Dell Edge Gateway Model 5000 (Commercial version - available Dec 2015)		Dell Edge Gateway Model 5100* (Industrial version - available Mar 2016)	
Environmental	Operating temperature 0°C to 50°C; Relative humidity 5% to 95% non-condensing		Operating temperature: Extended temperature range TBD; Relative humidity 5% to 95% non-condensing	
Dimensions	217 mm wide x 206 mm deep x 58 mm high (8.5 in x 8.1 in x 2.3 in)		217 mm wide x 206 mm deep x 73 mm high (8.5 in x 8.1 in x 2.9 in)	
Form Factor	Fanless design. Optimized for wall and DIN-rail mounting		Fanless design. Optimized for wall and DIN-rail mounting. Designed for industrial conditions	
Weight	Starting at 3.0 Kg		Starting at 3.2 Kg	
Processor	Intel® Atom™ E3825 1.33GHz 2 cores	Intel® Atom™ E3827 1.75GHz 2 cores	Intel® Atom™ E3825 1.33GHz 2 cores	Intel® Atom™ E3827 1.75GHz 2 cores
Memory	2G (4x256Mx16 DDR3L) 1067MHz	4G (8x 256Mx16 DDR3L) or 8G (8x 512Mx16 DDR3L) 1333MHz	2G (4x 256Mx16 DDR3L) 1067MHz	4G (8x 256Mx16 DDR3L) 1333MHz
Warranty and service ³	Commercial services vary. Limited hardware warranty with mail-in service; ProSupport with on-site service ² after remote diagnosis, up to 5 years. Custom factory integration service.		Commercial services vary. Limited hardware warranty ¹ with mail-in service; ProSupport with on-site service ² after remote diagnosis, up to 7 years. Custom factory integration service.	
Operating system	Factory options for Ubuntu Snappy Core and Wind River Linux. Windows 10 IoT Industry / LTSB*			
Security	Trusted Platform Module (TPM) v1.2 at launch and v2.0* in March 2016; Secure Boot, BIOS password and I/O port disablement. Chassis intrusion alerting via optional rugged enclosure*.			
Manageability	WindRiver: Helix Device Cloud. Ubuntu Snappy and Windows IoT Industry*: your choice of Cloud Client Manager (CCM) or Dell Client Command Suite to enable your choice of third-party on-premise management console such as Microsoft System Center.			
I/O	Dual Independent Gigabit Ethernet (RJ-45) USB: 2 x USB2, 1 x USB3 Serial Interfaces: 1 x RS-232, 2 x RS-485. 1 x RS-422/485. Optional CANbus card* Optional modular I/O expansion interface* 802.11n Wifi +Bluetooth Low Energy; WWAN (3G or LTE). Optional wireless mesh modules: IEEE 802.15.4 Zigbee/6LoWPAN combo module*, Z-Wave module* Plus ISV application support for diverse modern and legacy device connection protocols.			
Storage	Solid-state drive options (m.2 form factor): 32 GB or 64 GB options			
Video	One HDMI port			
Power Input	Nominal input 24V AC/DC (18 – 26.4V), 4.0 Amps. Optional expansion power module* Also accepts standard Dell notebook AC adapter, 65W, 7.4mm plug.			
5000 Series Accessories (Optional)	Optional expansion power module*, Optional I/O expansion module*, Optional IP65 rugged enclosure (built for Model 5700, validated with Model 5500)*			
Data integration and analytics	Available Dell Boomi and Statistica software for backend data integration and distributed analytics. Series 5000 gateways can also support third-party solutions, including offerings from our certified ISV partners.			
IoT Services	Optional IoT advisory consulting, configuration and applications development services. Custom configuration service (BIOS, your software image, etc.) available*.			
OEM / Co-branding	Yes, OEM ready. Talk to us about co-branding projects.			

*Available March 2016

Find more online at dell.com/loTgateway

1 For copy of Limited Hardware Warranty, write Dell USA LP, Attn: Warranties, One Dell Way, Round Rock, TX 7882 or see www.dell.com/warranty

2 Onsite Service after Remote Diagnosis: Remote Diagnosis is determination by online/phone technician of cause of issue; may involve customer access to inside of system and multiple or extended sessions. If issue is covered by Limited Hardware Warranty (www.dell.com/warranty) and not resolved remotely, technician and/or part will be dispatched, usually within 1 business day following completion of Remote Diagnosis. Availability varies. Other conditions apply.

3 Dell Services: availability and terms of Dell Services vary by region. For more information visit dell.com/servicesdescriptions.

