

Integrated Software Framework v2.00b

STANDARD FEATURES

- MPLAB® Harmony is a flexible, abstracted, fully integrated firmware development platform for PIC32 microcontrollers
- Broad range of Middleware Stack/Libraries, including: USB, TCP/IP, Wi-Fi™, File System, Graphics, Bootloaders, Bluetooth™, Audio, DSP, Math, Cryptography, Drivers, System Services, and more
- Over 160 Application Demonstrations with up to 600 application configurations to accelerate application development
- Seamlessly integrates third-party solutions (RTOS, Middleware, Drivers, etc.) into the software framework
- RTOS support, which includes: FreeRTOS™, OPENRTOS, Express Logic Thread X, SEGGER embOS®, Micrium® µC/OS-II™, Micrium µC/OS-III™
- Middleware support, which includes: SEGGER emWin®, InterNiche Technologies, Inc., wolfSSL, and PubNub®
- Both free and enabling license terms provided

For a detailed list of features, please visit the MPLAB Harmony Web page at:

www.microchip.com/harmony


From the landing page, scroll down and select the **Features** tab.

DESCRIPTION

MPLAB Harmony is a flexible, abstracted, fully integrated firmware development platform for PIC32 microcontrollers. MPLAB Harmony's modular architecture allows drivers and libraries to work together with minimal effort. It is scalable across PIC32 Microchip devices to custom fit customers' requirements.

MPLAB Harmony takes key elements of modular and object oriented design, adding an Operating System Abstraction Layer (OSAL) that provides the flexibility to use a Real-Time Operating System (RTOS) or work without one, and provides a framework of software modules that are easy to use, configurable for your specific needs, and that work together in complete harmony.

In addition, the MPLAB Harmony Configurator (MHC) and code development format allows for maximum reuse and reduces time to market.



COMPLIANCE

Compliant with MISRA-C:2012 Mandatory Standards:

- MPLAB Harmony Drivers, System Services, and Peripheral Libraries

DEVELOPMENT TOOLS

- MPLAB X IDE v3.30 or later is required
- MPLAB XC32 C/C++ Compiler v1.42 (ISO 26262)
- MPLAB X IDE plug-ins:
 - MPLAB Harmony Configurator (MHC) v2.00.xx

THIRD-PARTY DEVELOPERS

Microchip offers a range of documentation to assist you with the design of your own software offerings for MPLAB® Harmony. These documents, which are provided with the installation Help, are also available for download from the MPLAB Harmony website (see **“Download Information”** for details).

- MPLAB Harmony Overview
- MPLAB Harmony Compatibility Guide
- MPLAB Harmony Tutorial
- MPLAB Harmony Driver Development Guide
- MPLAB Harmony Configurator User's Guide
- MPLAB Harmony Configurator Developer's Guide
- MPLAB Harmony Graphics Composer User's Guide
- MPLAB Harmony Test Harness User's Guide
- MPLAB Harmony Compatibility Checklist Worksheet

MPLAB HARMONY v2.00b

v2.00b FEATURE UPDATES AND ADDITIONS0

MPLAB Harmony v2.0b includes the following updates and additions:

- Board Support Package (BSP) Creation tool (Alpha)
- Application templates (Beta)
- Initial microMIPS™ ISA support
- PIC32MZ DA MCU family support
- MISRA-C: 2012-compliant optimized peripheral libraries for all PIC32 MCUs
- TCP/IP Stack Library updates for Static drivers
- New applications for microphone support:
 - usb_headset
 - usb_microphone
- Updated Audio Codec drivers (microphone support and dynamic I²C)
- Updated applications for PIC32MZ audio
- Integrated Touch and Audio applications
- Tighter coupling between SEGGER emWin Pro and MPLAB Harmony:
 - SEGGER emWin tool suite
 - SEGGER emWin functional demonstration and user's guide
- AR1021 Resistive Touch Display Driver
- Revised JPEG decoder with integrated support for external media and display resize
- New application for SD card JPEG, BMP, and GIF decoding to display
- New application for MSD JPEG decoding, low-cost graphics board
- Updated touch drivers (MTCH6301, MTCH6303); improved touch system service
- Opus codec in universal decoders framework
- Support for double buffering (up to WQVGA resolution) in MPLAB Harmony Graphics Composer
- Updated support for WVGA display (LCCG Graphics Driver) on PIC32MZ family devices

Utilities:

- MHC and MPLAB Harmony Graphics Composer
 - Configuration Import/Export/Move/Copy
 - Updated pin management features

Please refer to the v2.00b Release Notes for additional information (see “[Download Information](#)”).

DOWNLOAD INFORMATION

MPLAB Harmony, including the current release notes and Software License Agreement, is available for download by visiting:

<http://www.microchip.com/mplabharmony>

ADDITIONAL RESOURCES

MPLAB Harmony TV offers a wide range of getting started and training videos. The video content is available by scrolling to the bottom of the MPLAB Harmony webpage at:

<http://www.microchip.com/mplabharmony>

The **Microchip Developer Site** provides short introductory videos, self-paced training modules, and answers to frequently asked questions.

<http://microchip.wikidot.com/harmony:start>

Note the following details of the code protection feature on Microchip devices:

- Microchip products meet the specification contained in their particular Microchip Data Sheet.
- Microchip believes that its family of products is one of the most secure families of its kind on the market today, when used in the intended manner and under normal conditions.
- There are dishonest and possibly illegal methods used to breach the code protection feature. All of these methods, to our knowledge, require using the Microchip products in a manner outside the operating specifications contained in Microchip's Data Sheets. Most likely, the person doing so is engaged in theft of intellectual property.
- Microchip is willing to work with the customer who is concerned about the integrity of their code.
- Neither Microchip nor any other semiconductor manufacturer can guarantee the security of their code. Code protection does not mean that we are guaranteeing the product as “unbreakable.”

Code protection is constantly evolving. We at Microchip are committed to continuously improving the code protection features of our products. Attempts to break Microchip's code protection feature may be a violation of the Digital Millennium Copyright Act. If such acts allow unauthorized access to your software or other copyrighted work, you may have a right to sue for relief under that Act.

Information contained in this publication regarding device applications and the like is provided only for your convenience and may be superseded by updates. It is your responsibility to ensure that your application meets with your specifications. MICROCHIP MAKES NO REPRESENTATIONS OR WARRANTIES OF ANY KIND WHETHER EXPRESS OR IMPLIED, WRITTEN OR ORAL, STATUTORY OR OTHERWISE, RELATED TO THE INFORMATION, INCLUDING BUT NOT LIMITED TO ITS CONDITION, QUALITY, PERFORMANCE, MERCHANTABILITY OR FITNESS FOR PURPOSE. Microchip disclaims all liability arising from this information and its use. Use of Microchip devices in life support and/or safety applications is entirely at the buyer's risk, and the buyer agrees to defend, indemnify and hold harmless Microchip from any and all damages, claims, suits, or expenses resulting from such use. No licenses are conveyed, implicitly or otherwise, under any Microchip intellectual property rights unless otherwise stated.

Microchip received ISO/TS-16949:2009 certification for its worldwide headquarters, design and wafer fabrication facilities in Chandler and Tempe, Arizona; Gresham, Oregon and design centers in California and India. The Company's quality system processes and procedures are for its PIC® MCUs and dsPIC® DSCs, KEELoc® code hopping devices, Serial EEPROMs, microperipherals, nonvolatile memory and analog products. In addition, Microchip's quality system for the design and manufacture of development systems is ISO 9001:2000 certified.

**QUALITY MANAGEMENT SYSTEM
CERTIFIED BY DNV
= ISO/TS 16949 =**

Trademarks

The Microchip name and logo, the Microchip logo, AnyRate, dsPIC, FlashFlex, flexPWR, Heldo, JukeBlox, KeeLoq, KeeLoq logo, Klear, LANCheck, LINK MD, MediaLB, MOST, MOST logo, MPLAB, OptoLyzer, PIC, PICSTART, PIC32 logo, RightTouch, SpyNIC, SST, SST Logo, SuperFlash and UNI/O are registered trademarks of Microchip Technology Incorporated in the U.S.A. and other countries.

ClockWorks, The Embedded Control Solutions Company, ETHERSYNCH, Hyper Speed Control, HyperLight Load, IntelliMOS, mTouch, Precision Edge, and QUIET-WIRE are registered trademarks of Microchip Technology Incorporated in the U.S.A.

Analog-for-the-Digital Age, Any Capacitor, AnyIn, AnyOut, BodyCom, chipKIT, chipKIT logo, CodeGuard, dsPICDEM, dsPICDEM.net, Dynamic Average Matching, DAM, ECAN, EtherGREEN, In-Circuit Serial Programming, ICSP, Inter-Chip Connectivity, JitterBlocker, KlearNet, KlearNet logo, MiWi, motorBench, MPASM, MPF, MPLAB Certified logo, MPLIB, MPLINK, MultiTRAK, NetDetach, Omniscient Code Generation, PICDEM, PICDEM.net, PICkit, PICtail, PureSilicon, RightTouch logo, REAL ICE, Ripple Blocker, Serial Quad I/O, SQL, SuperSwitcher, SuperSwitcher II, Total Endurance, TSHARC, USBCheck, VariSense, ViewSpan, WiperLock, Wireless DNA, and ZENA are trademarks of Microchip Technology Incorporated in the U.S.A. and other countries.

SQTP is a service mark of Microchip Technology Incorporated in the U.S.A.

Silicon Storage Technology is a registered trademark of Microchip Technology Inc. in other countries.

GestIC is a registered trademarks of Microchip Technology Germany II GmbH & Co. KG, a subsidiary of Microchip Technology Inc., in other countries.

All other trademarks mentioned herein are property of their respective companies.

© 2016, Microchip Technology Incorporated, Printed in the U.S.A., All Rights Reserved.

ISBN: