# **Activity Overview**

In this activity, you will create a triangle with a midsegment, measure a side and the midsegment, define variables, and prepare a spreadsheet to capture data from measurements.

### **Materials**

• Technology needed (TI-Nspire™ handheld, computer software)



# **Steps**

## Step 1: Preparing the document

- Open a new document by clicking on 命 > New Document > Add Notes.
- 2. Type: Triangle Midsegments.

Note: To obtain capital letters, press the fishift key, then the letter.

Press docv > File > Save As ....
Type: Triangle Midsegments.


Tab to [save] and press [enter].

Note: To obtain the underscore, press ctrl ......

- 4. To add a new page, press ctrl docv > Add Geometry.
- To hide the scale in the right corner of the screen, go to Menu > View > Hide Scale.
- 6. Press **Menu > Settings**. Select *Float 4* for display digits. Tab to OK and press or enter.









## Step 2: Drawing triangle ABC

- 1. Press Menu > Shapes > Triangle.
- 2. Press to place the first point of the triangle and immediately press shift A to label the point A.
- 3. Repeat steps to complete the triangle, labeling the other points *B* and *C*.
- 4. Press esc to exit the **Triangle** tool.

**Note:** If the labels were not created when the triangle was created, press **Menu > Actions > Text** to label the points.

# Step 3: Constructing midpoints of segments AB and AC

- 1. Press Menu > Construction > Midpoint.
- 2. Move cursor to side AB of the triangle until the word side appears. Press to construct the midpoint. Immediately label the point M.
- 3. Construct the midpoint N of side AC.
- 4. Press esc to exit the **Midpoint** tool.


## Step 4: Drawing the midsegment


- 1. Press Menu > Points & Lines > Segment.
- 2. Connect *M* and *N* by clicking on each point.
- 3. Press esc to exit the **Segment** tool.


# A C

## Step 5: Measuring the midsegment and BC

- 1. Press Menu > Measurement > Length.
- 2. Click segment *MN*. Move the measurement to a desirable location and press ( to place it.
- 3. To measure segment *BC*, move your cursor over the segment, and press tab until *side* appears. Press . Move the measurement to a desirable location.
- 4. Press esc to exit the **Measurement** tool.










## Step 6: Defining MN and BC as variables

- 1. Click once on the measurement of *MN* to highlight. Press ctrl var.
- 2. Type [\$\tilde{v}\$shift] [M] [\$\tilde{v}\$shift] [N] [enter] to define the variable.
- 3. Repeat to define variable BC.



## Step 7: Labeling columns

- Press ctrl docv > Add Lists & Spreadsheet to insert a spreadsheet page.
- 2. Move to the very top row above the diamond row. In Column A, type **Imn.** Press enter. (Since *MN* is defined as a variable, it cannot be used as the heading for the column nor can a space be included in the column heading.)
- 3. In Column B, type **lbc** for the heading. (the *l* is for *list*)

# # 11 12 13 \* Triangle Mi. ms > PAD (1) | PAD (

## Step 8: Defining columns to capture data

- 1. Move to the diamond row in Column A.
- 2. Press Menu > Data > Data Capture > Manual.
- 3. Type **mn** for the variable and press enter.
- 4. Move to the diamond row in Column B.
- 5. Press Menu > Data > Data Capture > Manual.
- 6. Type **bc** for the variable and press enter.

4	A Imn	B lbc	8	D	1
=	=capture(	paire(bc,0			
1					
24					
3					
4					
5					1/2

## Step 9: Saving the document

1. Press ctrl S.