



**QVGQ2.E244458**  
**Isolated Loop Circuit Protectors - Component**

[Page Bottom](#)

---

**Isolated Loop Circuit Protectors - Component**

[See General Information for Isolated Loop Circuit Protectors - Component](#)

**BRIGHTKING (SHENZHEN) CO LTD**

E244458

2nd Fl Tianan Management Center Bldg

Tian An Cyber Park

Futian District

Shenzhen, Guangdong 518040 CHINA

**BK series gas tubes, two electrode, Type 1**, Models BK1XX00702, BK1XX00702-M, BK13000702, BK13000702-M, YA-141N, BK1-141N, BK1XX01002, BK1XX01002-M, BK12001002, BK22001002-M, YA-201M, BK1-201M, BK1XX01502, BK1XX01502-M, BK12001502, BK22001502-M, YA-301M, BK1-301M, BK1XX02002, BK1XX02002-M, BK12002002, BK12002002-M, YA-401M, BK1-401M, BK1XX02502, BK1XX02502-M, BK12002502, BK22002502-M, YA-501M, BK1-501M, BK2XX00702, BK2XX00702-M, BK2XX07502, BK2XX07502-M, BK23000702, BK23000702-M, YS-141N, BK2-141N, BK2XX01002, BK2XX01002-M, BK2XX01102, BK2XX01102-M, BK22001002, BK22001002-M, YS-201M, BK2-201M, BK2XX01502, BK2XX01502-M, BK2XX03002, BK2XX03002-M, BK22001502, BK22001502-M, YS-301M, BK2-301M, BK2XX02002, BK2XX02002-M, BK2XX05002, BK2XX05002-M, BK22002002, BK22002002-M, YS-401M, BK2-401M, BK2XX02502, BK2XX02502-M, BK2XX03502, BK2XX03502-M, BK22002502, BK22002502-M, YS-501M, BK2-501M.(\$)

**BK series gas tubes, two electrode, Type 2**, Models BK1XX18002, BK1XX18002-M, BK1XX12002, BK1XX12002-M, BK1XX20002, BK1XX20002-M, BK1XX10002, BK1XX10002-M, BK1XX15002, BK1XX15002-M, BK1XX07502, BK1XX07502-M, BK1XX03002, BK1XX03002-M, BK1XX13502, BK1XX13502-M, BK1XX09002, BK1XX09002-M, BK1XX03502, BK1XX03502-M, BK1XX22502, BK1XX22502-M, BK1XX25002, BK1XX25002-M, BK1XX05002, BK1XX05002-M, BK3XX00702, BK3XX00702-M, BK3XX07502, BK3XX07502-M, BK33000702, BK33000702-M, YP-141N, BK3-141N, BK3XX01002, BK3XX01002-M, BK3XX01102, BK3XX01102-M, BK32001002, BK32001002-M, YP-201M, BK3-201M, BK3XX01502, BK3XX01502-M, BK3XX03002, BK3XX03002-M, BK32001502, BK32001502-M, YP-301M, BK3-301M, BK3XX02002, BK3XX02002-M, BK3XX03502, BK3XX03502-M, BK32002002, BK32002002-M, YP-401M, BK3-401M, BK3XX02502, BK3XX02502-M, BK3XX05002, BK3XX05002-M, BK32002502, BK32002502-M, YP-501M, BK3-501M.(\$)

## Notes:

(+) Indicates certain components per Series may experience a short circuit condition or voltage breakdown levels outside of their rated range if the components are placed in a circuit that is exposed to lightning events having a peak current of 10A or greater (ie: 10 x 1000 us waveform, 10 A peak).

(X\*) Suffix 'X' indicates Part Nos. may be followed by suffix S, L, E, T, A; Suffix "\*" indicates Part Nos. may be followed by suffix S, F, A, B, C, D.

(\* ) Indicates Part Nos. may be followed by suffix S.

(X) Indicates Part Nos. may be followed by suffix F, T, CF, S, Y.

(@) All models may be prefix or/and suffix with A thru Z or/and 0 thru 9 or/and any symbol, numbers, letters.

(\$ ) X = May be A thru Z or/and 0 thru 9 or/and any symbol, numbers, letters and all models may be prefix or/and suffix with A thru Z or/and 0 thru 9 or/and any symbol, numbers, letters.



Marking: Recognized company name or trademarks **B**, **C** or "C" or "ZOV", Component Recognition Mark and Part No. or Part Marking shall be placed on the product or smallest shipping package.

Last Updated on 2015-04-30

---

[Questions?](#)

[Print this page](#)

[Terms of Use](#)

[Page Top](#)

◆ 2015 UL LLC

When the UL Leaf Mark is on the product, or when the word "Environment" is included in the UL Mark, please search the [UL Environment database](#) for additional information regarding this product's certification.

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2015 UL LLC".